

The lightest sleeper drill in the range Lightweight and easy to use **Maximised** safety Reliability and long lifespan





Your benefits

- Easy and fast operation for all sleeper drilling applications
- Drilling precision is ensured by using the drill bushing
- Operational safety for on track use:
 - Adjustable drilling depth limitation to avoid contacting with the ballast under the sleeper
 - · Protective sheath on all the length
 - · Auger brake in case the drill jam into the sleeper
 - Self-unlocking auger holding chuck to quickly clear the track



Optional equipments

- Gear box for hard wood sleeper
- Auger holding chuck for cylindrical, graffenstaden or FS8489 drill bits

Specifications	
Engine	2 stroke - STIHL BT131
Engine power	1.4 kW (1.9 hp) 8,500 rpm
Mass (in working order)	Approx. 33 lbs. (14.9 kg)
Dimensions (without auger brake) (L x W x H)	21 x 15 x 35 in. (530 x 390 x 900 mm)
Maximum drilling depth	7.8 in. (200 mm)
Tool rotation speed	588 rpm
Maximal auger diameter	0.98 in. (25 mm)
Auger holding chuck diameter	0.63 in. (16 mm)

Accessories and maintenance kit

- Transport cases
- Drill brushing (different diameters available)
- Weight compensation trolley (different gauges available)
- Packs associated to the PTXL N07029, N05775, ST760B04, ST760B56 et ST761B02 :

SMART PACK (KEPTXLBT1311A	Maintenance kit – 1 year Engine BT131
UFEPPACK KUPTXL-01	Wear & Tear Kit – 01

Consumables

• Drill bits (different diameters available)

