



*The precision coachscrewing machine that ensures quality and traceability of tightening*



*Tightening torque precisely controlled  
Optimized working time  
Geolocated and recorded tightening*

### Your benefits

- Precise and repeatable tightening of coachscrews
- Increased efficiency thanks to automatic adjustment of the three tightening speeds
- Easy preselection of tightening torque and type of fastenings
- Torque and GPS tightening position recording for traceability according to the quality plan
- Ergonomic, adjustable and folding control handles
- Digital screen for easy configuration and control of the tightening torque



### Coachscrewing machine specifications

Engine	Honda GX200
Engine power	4.8 kW (6.5 ch)
Mass without trolley	234 lbs (106 kg)
Dimensions in operation (L x l x W)	81.7 x 21.3 x 36.7 in. (2,075 x 540 x 906 mm)
Dimensions in storage (L x l x W)	53.6 x 21.3 x 30.7 in. (1,360 x 540 x 780 mm)
Acoustic level	(Laeq) 84 dB(A) (Lwa) 100 dB(A)
Tightening torque	16 to 55 daN.m
Maximum untightening torque	110 daN.m
Output	~ 500 tightenings per hour

### Standard kit equipment

- Digital hydraulic coachscrewing machine
- Traversing or adherent trolley  
(several available dimensions)
- Lighting system
- Key support

### Consumables and accessories

- Sockets/wrenches  
(several available dimensions)
- Protective cover

