







BATTERY-POWERED RAIL DRILL

Your benefits

- A battery-powered stand-alone rail drill
- Easily transportable due to its reduced weight of 16.4 kg
- Quick and tool-free installation of Weldon's classic drills with the Click and Go system
- 2 speed settings suitable for drill bits and twist drills
- Drilling diameter from 7 to 40 mm
- Drilling gauge for longitudinal positioning (accessory)



- 1 Optimal ergonomics with only 16.4 kg in working order
- 2 Quick clamping device for Vignole and groove rails
- 3 LED lighting of the working area
- Slide mounted motor allows easy access to the drill and the use of the supplied 3-jaw chuck and long drill bits
- (5) 2 speed settings for optimum drilling with drill bits or twist drills
- 6 Plug and Play: no mixing of fuel, difficult starts or engine maintenance
- A lightweight, long-life battery with 12 Ah

Composition of the kit (N08024) Elements available separately from the kit

- 1 Narval drill (drill forms set according to rail profile, optional)
- Carrying case with compartments for storing tools and drills
- 5 L pressurized tank for cutting fluid
- 1 x 12 Ah battery (N07958)
- 1 charger (N08023). Input voltage 220 V single phase.
 Plug adapters included
- Service tools with ejector for standard drills and ejector for premium drills

Activion technology advantages

- Ideal for a confined work environment: tunnels, metros and underground areas
- Adapted to urban works due to reduced sound level
- Improved ergonomics due to vibration-reducing handles

	Principal characteristics	
	Max. drilling diameter	40 mm (1.58 in.)
	Drilling time	Between 12s and 60s according to diameter
	Max. rail hardness for standard drills	270 HB
	Max. rail hardness for premium drills	325 HB
	Tension	18 V
	Battery capacity	216 Wh
	Autonomy	≈ 28 holes of \emptyset 24 mm with one battery
	Battery charging time	≈2 h
	2 speed settings: Speed for drill bits Speed for twist drills	400 rpm 690 rpm
٠	Dimensions in working order (L x W x H)	580 x 145 x 420 mm (22.8 x 5.7 x 16.5 in.)
•	Mass in working order	16.4 kg (36 lbs)
	Mass (without battery)	14.6 kg (32 lbs)
	Spindle	Weldon 19.05 quick fastening Click & Go
	Protection class	IP23
	Operating temperatures	-18 to 50°C
	Hand-arm vibration level	2.3 m/s ²
	Pressurized tank capacity	5 L



